



## **UL SPECIFICATION**

- \* FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH.
- \* FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

## PARTS SPECIFICATIONS ITEM QTY DESCRIPTION

- A (1) SOCKET- UL LISTED/CSA CERTIFIED
  BASE=MEDIUM
  SOCKET=PORCELIN
  SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- B (1) LEAD WIRE- 8" FROM CANOPY UL LISTED/CSA CERTIFIED, AWG #18 150°C BLACK AND WHITE WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. FROM TOP OF SCROLL. (SEE CHART FOR COLOR).
- C (1) GROUND WIRE- 8" FROM CANOPY
  1/4 LAY COPPER GROUND WIRE.
  FROM TOP OF SCROLL.
  (SEE CHART FOR TINT).

INNOVATIONS LIGHTING

DESIGN COPYRIGHT - 11/12/2019

ALL RIGHTS RESERVED AND MAY

NOT BE DUPLICATED WITHOUT OUR

WRITTEN PERMISSION

NO.	PART NO.	DESCRIPTION	REQ.

NOTICE: ANY DESIGN OR OTHER INFORMATION HEREON DEVELOPED BY THIS COMPANY IS CONFIDENTIAL MATERIAL AND EXCLUSIVE PROPERTY OF THE LD. ALIYA CO. DISCLOS OR REPRODUCTION REQUIRES THE WRITTEN CONSENT OF THE L.D. ALIYA CO.

INNOVATIONS
CREATIVITY MEET.\* EVOLUTIONARY DE.\*IGN®

	DRAWN IN THIRD ANGLE	"mm" DIMENSION INDICATED IN [] DIMENSION IN [] IS FOR REF. ONLY					TIT	
		TOLERANCES (EXCEPT AS NOTED)						
	PROJECTION	DECIMAL	ANGULAR	FRACTIO	NAL	S	CALE	
	\$ D	NONE ±.031 X + 015	± 1/2°	± 1/32			1:3	PΑ
	WV	.XX ±.010	DATE	DRAWN BY	CHECKED	BY	APPROVED BY	ITE
	'	.XXX ±.005	3/31/2021	SSL	X		X	1116

1LT \		WALL	MOUNT	Γ
	PART NO.	WALL		REV.

ITEM NO. 342-1W-BK-CLW